

## EMC ZDM 25/250 E. ISO 6432 cylinders, double acting, piston 25 mm, stroke 250 mm

Item no. FL-ZDM-25/250-E

Manufacturer E.MC

EAN 4050571930684

ISO 6432 cylinders, double acting, piston 25 mm, stroke 250 mm

### TECHNICAL DATA

HS-Code 84123100

Weight 0.55 kg



### STANDARDS & COMPLIANCE

ISO 6432

### DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305, seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm] 25

Stroke [mm] 250

| Version                 | Standard  |
|-------------------------|-----------|
| A (piston rod thread)   | M 10x1,25 |
| B (fastening thread)    | M 22x1,5  |
| G (compressed air port) | G 1/8"    |
| A1 [mm]                 | 10        |
| C [mm]                  | 34,0      |
| D [mm]                  | 16        |
| E [mm]                  | 8         |
| F [mm]                  | 22        |
| G [mm]                  | 104       |
| K [mm]                  | 28        |
| L [mm]                  | 22        |
| M [mm]                  | 137       |
| N [mm]                  | 12        |
| P [mm]                  | 65        |
| CH [mm]                 | 8         |