

EMC ZDPM 20/160 E. ISO 6432 cylinders, double acting, piston 20 mm, stroke 160 mm

Item no. FL-ZDPM-20/160-E

Manufacturer E.MC

EAN 4050571930899

ISO 6432 cylinders, double acting, piston 20 mm, stroke 160 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.31 kg



STANDARDS & COMPLIANCE

ISO 6432

DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: 1.4305, seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	20
Stroke [mm]	160

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	adjustable end position damping
A (piston rod thread)	M 8
B (fastening thread)	M 22x1,5
G (compressed air port)	G 1/8"
A1 [mm]	8
C [mm]	29,0
D [mm]	16
E [mm]	8
F [mm]	20
G [mm]	95
K [mm]	24
L [mm]	20
M [mm]	126
N [mm]	12
P [mm]	62
CH [mm]	6