

LE 16/100 CG. Guiding unit for ISO6432-12 & 16mm, stroke 100mm

Item no. FL-LE-16/100-CG

Manufacturer Fluidics equipment

EAN 4050571463656

Guiding unit for ISO6432-Ø 12 & 16mm, stroke 100mm

TECHNICAL DATA

HS-Code	84123100
Weight	0.4 kg



STANDARDS & COMPLIANCE

ISO6432

DESCRIPTION

Function:

Guide units are used for anti-rotation safety and absorbing side forces with standard cylinders.

Materials:

Body: anodized aluminium, guide rods: hard chromium plated steel, wiper: NBR, bearing: steel or sintered bronze

Temperature range:

-30 to +100 °C

Version	C with sliding guide
for piston diameter [mm]	12 & 16
Stroke [mm]	100
MA / MB* [Nm]	6 / 5
A [mm]	69
B [mm]	30
C [mm]	30

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

CH [mm]	8
D [mm]	12
D1 [mm]	6
E1 [mm]	19,50
F [mm]	66
G [mm]	29
H [mm]	10
I [mm]	10
J	M 4
K	M 4
L5 [mm]	66,5
L6 [mm]	13
L7 [mm]	38
M [mm]	32
N [mm]	4,5
O [mm]	6
P [mm]	8
Q [mm]	4,5
R [mm]	5,5
S	9
T [mm]	5,5
U [mm]	24
V [mm]	58
W1 [mm]	25,0
X [mm]	18
Y [mm]	22
Z [mm]	49,5