

# LE 16/500 HG. Guiding unit for ISO6432-12 & 16mm, stroke 500mm

<b>Item no.</b>	FL-LE-16/500-HG	<b>Manufacturer</b>	Fluidics equipment
<b>Manufacturer no.</b>	LE 16/500 HG	<b>EAN</b>	4050571463861

Guiding unit for ISO6432-Ø 12 & 16mm, stroke 500mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>1 kg</b>



## STANDARDS & COMPLIANCE

**ISO6432**

## DESCRIPTION

Function:

Guide units are used for anti-rotation safety and absorbing side forces with standard cylinders.

Materials:

Body: anodized aluminium, guide rods: hard chromium plated steel, wiper: NBR, bearing: steel or sintered bronze

Temperature range:

-30 to +100 °C

Version	H with sliding guide
for piston diameter [mm]	12 & 16
Stroke [mm]	500
MA / MB* [Nm]	6 / 5
A [mm]	69
B [mm]	30
C [mm]	30
CH [mm]	8

D [mm]	12
D1 [mm]	6
E [mm]	8
F [mm]	66
G [mm]	29
H [mm]	10
I [mm]	10
J	M 4
K	M 4
L1 [mm]	123,5
L2 [mm]	29
L3 [mm]	46
L4 [mm]	68
M [mm]	32
N [mm]	4,5
O [mm]	6
P [mm]	8
Q [mm]	4,5
R [mm]	5,5
S	9
T [mm]	5,5
U [mm]	24
V [mm]	58
W [mm]	18
X [mm]	18
Y [mm]	22
Z [mm]	49,5