

LE 50/100 HK. Guide unit for ISO15552-50mm, stroke 100mm

Item no. FL-LE-50/100-HK

Manufacturer Fluidics equipment

EAN 4050571465278

Guide unit for ISO15552-Ø 50mm, stroke 100mm

TECHNICAL DATA

HS-Code	84123100
Weight	4 kg



STANDARDS & COMPLIANCE

ISO15552

DESCRIPTION

Function:

Guide units are used for anti-rotation safety and absorbing side forces with standard cylinders.

Materials:

Body: anodized aluminium, guide rods: hard chromium plated steel, wiper: NBR, bearing: steel or sintered bronze

Temperature range:

-30 to +100 °C

Version	H with ball guide
for piston diameter [mm]	50
Stroke [mm]	100
MA / MB* [Nm]	42 / 38
A [mm]	137
B [mm]	70
C [mm]	70,2

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

CH [mm]	20
D [mm]	34
E [mm]	18,8
F [mm]	134
G [mm]	65
H [mm]	15
I [mm]	20
L1 [mm]	223
L2 [mm]	18
L3 [mm]	78
L4 [mm]	148
N [mm]	9,0
O [mm]	16
P [mm]	15
Q [mm]	8,5
S	M 8
T [mm]	100
U [mm]	85
V [mm]	46,5
Z [mm]	104