

# LZ 63/2500 REP. Reparatursatz für Kolbenstangenlose Zylinder

<b>Item no.</b>	<b>FL-LZ-63/2500-REP</b>	<b>Manufacturer</b>	<b>Fluidics equipment</b>
<b>Manufacturer no.</b>	<b>LZ 63/2500 REP</b>	<b>EAN</b>	<b>4050571469856</b>

Reparatursatz für Kolben-stangenlose Zylinder

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>175 kg</b>



## DESCRIPTION

Construction type:

Rodless cylinder with direct force reduction through the pipe-slit on the yoke, both sides with adjustable end position damping, can be swapped with many other manufacturers

Materials:

Cylinder tubes, cylinder heads and drive rollers: anodized aluminium, seals: NBR / PUR, masking tape: Stainless steel

Temperature range:

-20 to +80 °C

Operating pressure:

max. 8 bar

Stroke:

at will up to 6,000 mm

Installation position:

arbitrarily, however, preferably yoke downward to avoid soiling.

Compressed air connection:

both sides (anytime by removing closing plugs on one side or below, or combinations thereof can be

reconstructed)

Version:

With Magnetic piston

Cylinder switch type:

D, A (Ø 18: D or A in combination with fastening AB2)

Piston diameter [mm] 63

Version                      Repair set (with all wear parts for stroke up to 2500 mm)