

LZFF 32/700. Kolbenstangenloser Zylinder, Kolben 32 mm, Hub 700 mm

Item no. FL-LZFF-32/700 **Manufacturer** Fluidics equipment

Manufacturer no. LZFF 32/700 **EAN** 4050571819927

Kolbenstangenloser Zylinder, Kolben Ø 32 mm, Hub 700 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	1 kg



DESCRIPTION

Construction type:

Rodless cylinder with direct force reduction through the pipe-slit on the yoke, both sides with adjustable end position damping, can be swapped with many other manufacturers

Materials:

Cylinder tubes, cylinder heads and drive rollers: anodized aluminium, seals: NBR / PUR, masking tape: Stainless steel

Temperature range:

-20 to +80 °C

Operating pressure:

max. 8 bar

Stroke:

at will up to 6,000 mm

Installation position:

arbitrarily, however, preferably yoke downward to avoid soiling.

Compressed air connection:

both sides (anytime by removing closing plugs on one side or below, or combinations thereof can be

reconstructed)

Version:

With Magnetic piston

Cylinder switch type:

D, A (Ø 18: D or A in combination with fastening AB2)

Piston diameter [mm]	32
Stroke [mm]	700
Version	with double sliding guide for large loads
D (compressed air port)	G 1/8"
Repair sets (with all wear parts)	LZ 32/2500 REP
Repair sets (only damping ring and grooved ring)	LZ 32 REP
lateral force permissible [N]	1035
A [mm]	120
A1 [mm]	77,5
AF [mm]	100
AF1 [mm]	35
AM [mm]	16
B [mm]	55
E [mm]	171
E1 [mm]	86
F [mm]	140
F1 [mm]	55
G [mm]	70
J [mm]	4,5
M [mm]	25,0
MF [mm]	80
N	M 5
N1 [mm]	9,0
O [mm]	5,5
OP [mm]	5,3
S [mm]	41,0
T	M 5
T1 [mm]	10
U [mm]	52
W [mm]	65,0
WF [mm]	78
Damper length [mm]	24