

ND 100/40. Short-stroke cylinders, double acting, piston 100 mm, stroke 40 mm

Item no. FL-ND-100/40

Manufacturer Fluidics equipment

EAN 4050571522711

Short-stroke cylinders, double acting, piston 100 mm, stroke 40 mm

TECHNICAL DATA

HS-Code 84799070

Weight 2.4 kg



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	100
Stroke [mm]	40
Version	without magnetic piston
C1 (piston rod thread)	M 12
P (compressed air port)	G 1/4"
Repair sets	ND 100 REP
A [mm]	131,0
B [mm]	124

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D [mm]	25
F [mm]	11,0
G [mm]	17,2
H [mm]	69,0
I [mm]	103
J [mm]	16,0
K [mm]	103,0
L [mm]	56,0
N [mm]	94,0
Q [mm]	11,0
S [mm]	124,0
T [mm]	20
V [mm]	22
W [mm]	10,0
X [mm]	80
Y [mm]	30
Z [mm]	50
AA [mm]	20,5
AB [mm]	14