

ND 40/25. Short-stroke cylinders, double acting, piston 40 mm, stroke 25 mm

Item no. FL-ND-40/25

Manufacturer Fluidics equipment

EAN 4050571523275

Short-stroke cylinders, double acting, piston 40 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84799070

Weight 0.29 kg



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	40
Stroke [mm]	25
Version	without magnetic piston
C1 (piston rod thread)	M 6
P (compressed air port)	G 1/8"
Repair sets	ND 40 REP
A [mm]	58,0

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

B [mm]	55
D [mm]	12
F [mm]	5,8
G [mm]	9,0
H [mm]	30,5
I [mm]	42
J [mm]	11,0
K [mm]	42,0
L [mm]	29,5
N [mm]	40,0
Q [mm]	5,7
S [mm]	55,0
T [mm]	12
V [mm]	10
W [mm]	6,0
X [mm]	33
Y [mm]	17
Z [mm]	20
AA [mm]	12,5
AB [mm]	10