

ND 63/100. Short-stroke cylinders, double acting, piston 63 mm, stroke 100 mm

Item no. FL-ND-63/100

Manufacturer Fluidics equipment

EAN 4050571523473

Short-stroke cylinders, double acting, piston 63 mm, stroke 100 mm

TECHNICAL DATA

HS-Code 84799070

Weight 1.2 kg



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	63
Stroke [mm]	100
Version	without magnetic piston
C1 (piston rod thread)	M 8
P (compressed air port)	G 1/8"
Repair sets	ND 63 REP
A [mm]	86,0
B [mm]	80

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D [mm]	16
F [mm]	9,0
G [mm]	14,0
H [mm]	46,0
I [mm]	62
J [mm]	11,0
K [mm]	62,0
L [mm]	37,0
N [mm]	60,0
Q [mm]	8,8
S [mm]	80,0
T [mm]	14
V [mm]	13
W [mm]	7,0
X [mm]	50
Y [mm]	22
Z [mm]	30
AA [mm]	15,0
AB [mm]	12