

ND 80/10. Short-stroke cylinders, double acting, piston 80 mm, stroke 10 mm

Item no. FL-ND-80/10

Manufacturer Fluidics equipment

EAN 4050571523572

Short-stroke cylinders, double acting, piston 80 mm, stroke 10 mm

TECHNICAL DATA

HS-Code 84799070

Weight 1 kg



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	80
Stroke [mm]	10
Version	without magnetic piston
C1 (piston rod thread)	M 10
P (compressed air port)	G 1/4"
Repair sets	ND 80 REP
A [mm]	105,0

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

B [mm]	100
D [mm]	20
F [mm]	9,0
G [mm]	14,0
H [mm]	55,0
I [mm]	82
J [mm]	14,0
K [mm]	82,0
L [mm]	46,0
N [mm]	77,0
Q [mm]	9,0
S [mm]	100,0
T [mm]	15
V [mm]	17
W [mm]	8,0
X [mm]	65
Y [mm]	28
Z [mm]	50
AA [mm]	18,0
AB [mm]	14