

NDM 40/60. Short-stroke cylinders, double acting, piston 40 mm, stroke 60 mm

Item no. FL-NDM-40/60 **Manufacturer** Fluidics equipment

Manufacturer no. NDM 40/60 **EAN** 4050571524593

Short-stroke cylinders, double acting, piston 40 mm, stroke 60 mm

TECHNICAL DATA



Article authenticity **Original product**

Condition of article **New**

HS-Code **84799070**

Weight **5 kg**

DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm] 40
 Stroke [mm] 60
 Version with magnetic piston
 C1 (piston rod thread) M 6
 P (compressed air port) G 1/8"
 Repair sets [ND 40 REP](#)
 A [mm] 58,0
 B [mm] 55
 D [mm] 12

E [mm]	28,0
F [mm]	5,8
G [mm]	9,0
H [mm]	30,5
I [mm]	42
J [mm]	11,0
K [mm]	42,0
L [mm]	39,5
N [mm]	40,0
Q [mm]	5,7
S [mm]	55,0
T [mm]	12
U [mm]	6,0
V [mm]	10
W [mm]	6,5
X [mm]	33
Y [mm]	17
Z [mm]	20
AA [mm]	12,5
AB [mm]	10