

NDM 50/25. Short-stroke cylinders, double acting, piston 50 mm, stroke 25 mm

Item no. FL-NDM-50/25

Manufacturer Fluidics equipment

EAN 4050571524692

Short-stroke cylinders, double acting, piston 50 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84799070

Weight 0.55 kg



DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	50
Stroke [mm]	25
Version	with magnetic piston
C1 (piston rod thread)	M 8
P (compressed air port)	G 1/8"
Repair sets	ND 50 REP
A [mm]	70,0
B [mm]	65

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D [mm]	16
E [mm]	34,0
F [mm]	6,8
G [mm]	11,0
H [mm]	37,5
I [mm]	50
J [mm]	11,5
K [mm]	50,0
L [mm]	39,5
N [mm]	50,0
Q [mm]	6,8
S [mm]	65,0
T [mm]	12
U [mm]	6,0
V [mm]	13
W [mm]	7,5
X [mm]	42
Y [mm]	22
Z [mm]	30
AA [mm]	13,5
AB [mm]	12