

NE 32/20. Short-stroke cylinders, single acting, piston 32 mm, stroke 20 mm

Item no. FL-NE-32/20 **Manufacturer** Fluidics equipment

Manufacturer no. NE 32/20 **EAN** 4050571525316

Short-stroke cylinders, single acting, piston 32 mm, stroke 20 mm

TECHNICAL DATA



Article authenticity **Original product**

Condition of article **New**

HS-Code **84799070**

Weight **22 kg**

DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

Piston diameter [mm]	32
Stroke [mm]	20
Version	without magnetic piston
C1 (piston rod thread)	M 6
P (compressed air port)	G 1/8"
A [mm]	51,0
B [mm]	46
D [mm]	12
F [mm]	5,8

G [mm]	9,0
H [mm]	27,0
I [mm]	32
J [mm]	11,5
K [mm]	36,0
L [mm]	29,5
N [mm]	34,0
Q [mm]	5,7
S [mm]	48,0
T [mm]	12
V [mm]	10
W [mm]	6,0
X [mm]	28
Y [mm]	17
Z [mm]	20
AA [mm]	11,0
AB [mm]	10