

## NE 80/25. Short-stroke cylinders, single acting, piston 80 mm, stroke 25 mm

Item no. FL-NE-80/25

Manufacturer Fluidics equipment

EAN 4050571525613

Short-stroke cylinders, single acting, piston 80 mm, stroke 25 mm

### TECHNICAL DATA

HS-Code 84799070

Weight 1.2 kg



### DESCRIPTION

Materials:

Head and base plate: Anodised aluminium / brass, cylinder tube: Anodised aluminium, piston rod: 1.4305 seal: NBR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Cylinder switch type:

G

|                         |                         |
|-------------------------|-------------------------|
| Piston diameter [mm]    | 80                      |
| Stroke [mm]             | 25                      |
| Version                 | without magnetic piston |
| C1 (piston rod thread)  | M 10                    |
| P (compressed air port) | G 1/4"                  |
| A [mm]                  | 105,0                   |
| B [mm]                  | 100                     |

**esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|         |       |
|---------|-------|
| D [mm]  | 20    |
| F [mm]  | 9,0   |
| G [mm]  | 14,0  |
| H [mm]  | 55,0  |
| I [mm]  | 82    |
| J [mm]  | 14,0  |
| K [mm]  | 82,0  |
| L [mm]  | 46,0  |
| N [mm]  | 77,0  |
| Q [mm]  | 9,0   |
| S [mm]  | 100,0 |
| T [mm]  | 15    |
| V [mm]  | 17    |
| W [mm]  | 8,0   |
| X [mm]  | 65    |
| Y [mm]  | 28    |
| Z [mm]  | 50    |
| AA [mm] | 18,0  |
| AB [mm] | 14    |