

R 12-2 VU. Vacuum regulator without external leakage G 1/2"

Item no. FL-R-12-2-VU

Manufacturer Fluidics equipment

EAN 4050571565534

Vacuum regulator without external leakage G 1/2"

TECHNICAL DATA

HS-Code **84141089**

Weight **2.1 kg**



DESCRIPTION

Application:

A vacuum without external leakage can be accurately regulated with these vacuum regulators. They are used in vacuum systems where individual consumer units need to be supplied with different levels of vacuum.

Adjustment:

The configuration is carried out using a knurled screw or via a pneumatic signal.

Materials:

Body: Anodized aluminium, seals: NBR

Temperature range:

-10 to +80 °C

Pressure gauge connection:

G 1/4" (controller G 1/4" and G 3/8": G 1/8")

Control connection (pneumatic setting):

G 1/8" (controller G 1 1/2": G 1/4")

Version

Precision regulator

Setting

Manually

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Thread	G 1/2"
Suction performance [m³/h]	20
Suction performance [l/min]	333
Pressure gauge connection	G 1/4"
Pressure regulation range [bar]	-1 to -0,02