

TM 125/200. ISO 15552 cylinders, piston 125 mm, stroke 200 mm, ECO

Item no. FL-TM-125/200

Manufacturer Fluidics equipment

EAN 4050571698324

ISO 15552 cylinders, piston 125 mm, stroke 200 mm, ECO

TECHNICAL DATA

HS-Code 84799070

Weight 8 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium section tube, Piston rod: Steel, hard chrome-plated, piston: Aluminium, Gasket: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A, Ø 125 and larger: C in combination with fastening C1 or C in combination with fastening C2

Piston diameter [mm] 125

Stroke [mm] 200

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

A (piston rod thread)	M 27x2
G (compressed air port)	G 1/2"
Repair sets	TM 125 REP
B [mm]	32
C [mm]	60
D [mm]	40
F [mm]	54
G [mm]	65
H [mm]	225
K [mm]	5,0
M [mm]	140,0
N [mm]	110,0
CH [mm]	27
RT	M 12