

Connecting cable 5 m with rectangular plug H and single cores - Festo KAB H 5

Item no. FL-KAB-H-5

Manufacturer Festo

Ready-assembled connecting cable with rectangular plug H (6.7 x 4.2) on one side and two open cable ends on the other, cable length 5 m. The two single cores of 0.17 mm² form the standard version for connecting Festo valves and are rated up to 60 V DC at 3 A. Degree of protection IP 40, -5 °C to +60 °C.

TECHNICAL DATA

HS-Code 85444290

Series KAB

Weight 0.033 kg



DESCRIPTION

A valve is only fitted once the electrical side is done as well. This 5 m cable already carries the rectangular plug H in the 6.7 x 4.2 pattern and ends in two open cores that can be wired straight to a terminal or controller.

- Two single cores of 0.17 mm², the standard version of this range
- Cable length 5 m, pre-assembled and ready to use without rework
- Rectangular plug H with 6.7 x 4.2 pattern for connecting Festo valves
- Clear core identification, pin 1 red and pin 3 black
- Rated for up to 60 V DC and 3 A, degree of protection IP 40

TECHNICAL DATA

Type designation	KAB H 5
Cable length	5 m
Connection	Rectangular plug H (6.7 x 4.2)
Opposite end	2 open cable ends
Cable	2 x 0.17 mm ² as single cores
Core assignment	Pin 1 red, pin 3 black, pin 2 not assigned
Voltage	max. 60 V DC

Current	max. 3 A
Degree of protection	IP 40
Temperature range	-5 °C to +60 °C

The cable is mainly used for connecting Festo valves. The version with two single cores is the standard choice. For purely static installation the two-core PUR cable is available as an alternative.