

Quick connect coupling SP-V-A Cupla 6P-V-A, brass - Nitto Kohki 459863874

Item no. NKH-459863874

Manufacturer Nitto Kohki

The plug of the SP-V-A Cupla has its own automatic shut-off valve and keeps the attached line tight down to 1.3×10^{-1} Pa when disconnected. A straight guide inside gives the valve a stable movement during coupling and uncoupling. Depending on size the minimum cross-sectional area is between 18 and 110 mm². Model 6P-V-A, brass, Seal material FKM.

TECHNICAL DATA

Betriebsdruck max [bar] **75.000000**

Weight **0.05 kg**

Werkstoff **Messing**


DESCRIPTION

When refrigerant circuits are evacuated and charged, an open line must neither draw in air nor lose fluid. SP-V-A Cupla carries an automatic shut-off valve in both socket and plug and stays vacuum tight down to 1.3×10^{-1} Pa even when disconnected.

- Two-way shut-off with an automatic valve in socket and plug, so both halves close by themselves on disconnection.
- Suitable for vacuum service down to 1.3×10^{-1} Pa (1×10^{-3} mmHg) even when disconnected, with a straight guide that stabilises valve movement.
- Working pressure of 3.0 to 7.5 MPa (31 to 76 kgf/cm²), with 1/4 and 3/8 inch reaching 7.5 MPa and 1/2 and 3/4 inch reaching 4.5 MPa.
- Three standard seal materials, CR for -20 to +80 °C, HNBR for -20 to +120 °C and FKM for -20 to +180 °C.
- HNBR resists HFC-134a, HFC-407C, HFC-410A and HFC-404A as well as PAG and ester type oils, while CR is aimed at HCFC-22 and HFC-134a.
- Low air admixture on connection, 1.0 mL on 2SP-V, 2.4 mL on 3SP-V, 3.2 mL on 4SP-V and 10.5 mL on 6SP-V.

TECHNICAL DATA

Model

6P-V-A

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Coupling part	plug
Body material	brass
Seal material	FKM
Working pressure	3.0 to 7.5 MPa (75 bar)
Valve structure	Two-way shut-off
Article number	459863874

APPLICATIONS

- Air conditioner production lines with refrigerant charging
- Refrigerator and refrigeration equipment production lines
- Evacuating circuits before they are filled
- Inert gas, gas and compressed air lines
- Test and filling stations running water or air

COMPATIBILITY

Socket and plug must be of the same size, since different sizes cannot be connected. Connection to SP Cupla Type A is possible provided the resulting flow rate reduction is taken into account, and once coupled the fluid may flow from either the plug or the socket side.

STANDARDS AND COMPLIANCE

Ends are supplied as R 1/4 to R 3/4 male threads and Rc 1/4 to Rc 3/4 female threads, maximum tightening torques run from 9 to 50 Nm on brass and from 14 to 90 Nm on stainless steel, and the seal materials are chloroprene rubber (CR), fluoro rubber (FKM) and hydrogenated nitrile rubber (HNBR).