

## ESD Coil Cord 1 M $\Omega$ , black, 1.8 m, 3/10 mm snap

Item no. WL24929

Manufacturer Safeguard

Highly elastic coiled grounding cord for personnel grounding at the ESD workstation with a built-in 1 M $\Omega$  safety resistor. Links the wrist strap (3 mm snap) to the ground point (10 mm snap), stretching to 1.8 m. Tested to BGI 818:2001.

### TECHNICAL DATA

|                   |                         |
|-------------------|-------------------------|
| Ausführungsklasse | <b>ESD (antistatic)</b> |
| Certification     | <b>IEC 61340-5-1</b>    |
| Colour            | <b>Black</b>            |
| HS-Code           | <b>85444290</b>         |
| Sales unit        | <b>1 Stück</b>          |
| Weight            | <b>0.1 kg</b>           |



### STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

### DESCRIPTION

The Safeguard ESD coil cord drains charge from the operator to ground in a controlled way, protecting electrostatic-sensitive devices at the ESD workstation (EPA). The integrated 1 M $\Omega$  safety resistor limits the leakage current for personnel-safe grounding.

### BENEFITS

- 1 M $\Omega$  safety resistor for controlled charge dissipation
- Highly elastic coiled form stretches to 1.8 m and keeps the operator free to move
- 3 mm snap at the wrist strap, 10 mm snap at the ground point

### TECHNICAL DATA

- Electrical resistance: 1 M $\Omega$
- Stretched length: 1.8 m
- Connection: 3 / 10 mm snap
- Colour: black
- Selling unit: piece

## **APPLICATION**

For grounding wrist straps with a 3-4 mm snap at ESD workstations in electronics manufacturing, repair and laboratory work.

## **STANDARDS AND COMPLIANCE**

Tested to BGI 818:2001. Supports an EPA built to IEC 61340-5-1.