

ESD Coil Cord 1 M Ω , black, 3.6 m, 3/10 mm snap - Safeguard WL42072

Item no. WL42072

Manufacturer Safeguard

Coiled grounding cord for personnel grounding at the ESD workstation with a built-in 1 M Ω safety resistor. Links the wrist strap (3 mm snap) to the ground point (10 mm snap), stretching to 3.6 m. Tested to BGI 818:2001.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Black
HS-Code	85444290
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Safeguard ESD coil cord drains charge from the operator to ground in a controlled way, protecting electrostatic-sensitive devices at the ESD workstation (EPA). The integrated 1 M Ω safety resistor limits the leakage current for personnel-safe grounding.

BENEFITS

- 1 M Ω safety resistor for controlled charge dissipation
- Coiled form stretches to 3.6 m and keeps the operator free to move
- 3 mm snap at the wrist strap, 10 mm snap at the ground point

TECHNICAL DATA

- Electrical resistance: 1 M Ω
- Stretched length: 3.6 m
- Connection: 3 / 10 mm snap
- Colour: black
- Selling unit: piece

APPLICATION

For grounding wrist straps with a 3-4 mm snap at ESD workstations in electronics manufacturing, repair and laboratory work.

STANDARDS AND COMPLIANCE

Tested to BGI 818:2001. Supports an EPA built to IEC 61340-5-1.