

ESD coiled cord 1 MΩ, yellow, 3.6 m, 3/10 mm snap - Safeguard WL42073

Item no. WL42073

Manufacturer Safeguard

ESD coiled cord for grounding wrist straps inside the EPA. Yellow version with a built-in 1 MΩ safety resistor, 3/10 mm snap fastener and 3.6 m working length for reliable personnel grounding.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Yellow
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This Safeguard ESD coiled cord connects a wrist strap to the EPA grounding point and dissipates personnel-bound electrostatic charges in a controlled way. The integrated 1 MΩ safety resistor limits the leakage current and protects the wearer.

BENEFITS

- Reliable personnel grounding with a defined 1 MΩ resistance
- Stretchable coiled form for full freedom of movement
- High-visibility yellow version

TECHNICAL DATA

- Electrical resistance: 1 MΩ
- Length: 3600 mm (3.6 m)
- Connection: 3 / 10 mm snap fastener
- Colour: yellow
- Tested to BGI 818:2001
- Selling unit: 1 piece

APPLICATION

For grounding ESD wrist straps at workstations in electronics manufacturing, assembly and repair.

STANDARDS AND COMPLIANCE

Suitable for use in EPA areas to IEC 61340-5-1.