

## ESD coiled cord 1 M $\Omega$ , black, 3.6 m, 7/10 mm snap - Safeguard WL42074

Item no. WL42074

Manufacturer Safeguard

ESD coiled cord for grounding wrist straps inside the EPA. Black version with a 1 M $\Omega$  safety resistor, 7/10 mm snap fastener and 3.6 m working length for reliable personnel grounding.

### TECHNICAL DATA

|                   |                  |
|-------------------|------------------|
| Ausführungsklasse | ESD (antistatic) |
| Colour            | Black            |
| Norm              | IEC 61340-5-1    |
| Sales unit        | 1 Stück          |
| Weight            | 0.1 kg           |



### STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

### DESCRIPTION

This Safeguard ESD coiled cord connects a wrist strap to the EPA grounding point and dissipates personnel-bound electrostatic charges in a controlled way. The integrated 1 M $\Omega$  safety resistor limits the leakage current and protects the wearer.

### BENEFITS

- Reliable personnel grounding with a defined 1 M $\Omega$  resistance
- Stretchable coiled form for full freedom of movement
- Extended reach with 3.6 m working length

### TECHNICAL DATA

- Electrical resistance: 1 M $\Omega$
- Length: 3600 mm (3.6 m)
- Connection: 7 / 10 mm snap fastener
- Colour: black
- Tested to BGI 818:2001
- Selling unit: 1 piece

## **APPLICATION**

For grounding ESD wrist straps at workstations in electronics manufacturing, assembly and repair.

## **STANDARDS AND COMPLIANCE**

Suitable for use in EPA areas to IEC 61340-5-1.