

ESD coiled cord 1 M Ω , black, 2.4 m, 10/10 mm snap

Item no. WL42068

Manufacturer Safeguard

ESD coiled cord for grounding wrist straps inside the EPA. Black version with a 1 M Ω safety resistor, 10/10 mm snap fastener and 2.4 m working length for reliable personnel grounding.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Colour	Black
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This Safeguard ESD coiled cord connects a wrist strap to the EPA grounding point and dissipates personnel-bound electrostatic charges in a controlled way. The integrated 1 M Ω safety resistor limits the leakage current and protects the wearer.

BENEFITS

- Reliable personnel grounding with a defined 1 M Ω resistance
- Stretchable coiled form for full freedom of movement
- 10/10 mm snap fastener for common grounding points

TECHNICAL DATA

- Electrical resistance: 1 M Ω
- Length: 2400 mm (2.4 m)
- Connection: 10 / 10 mm snap fastener
- Colour: black
- Tested to BGI 818:2001
- Selling unit: 1 piece

APPLICATION

For grounding ESD wrist straps at workstations in electronics manufacturing, assembly and repair.

STANDARDS AND COMPLIANCE

Suitable for use in EPA areas to IEC 61340-5-1.