

ESD coiled cord, highly elastic, 1 MOhm, 3 mm snap to banana socket, 3.6 m, black - Safeguard WL42104

Item no. WL42104**Manufacturer Safeguard**

Highly elastic ESD grounding cord for personnel grounding in the EPA. 3 mm snap for the wrist strap, banana socket on the ground side, extends to 3.6 m. Built-in 1 MOhm safety resistor.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Black
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This highly elastic ESD coiled cord connects an ESD wrist strap to the ground point and drains charges in a controlled way. The longer 3.6 m reach gives more freedom of movement at the bench.

BENEFITS

- Built-in 1 MOhm safety resistor limits the discharge current
- Highly elastic coil extends to 3.6 m and retracts
- 3 mm snap for 3-4 mm snap fittings, banana socket on the ground side

TECHNICAL DATA

- Electrical resistance: 1 MOhm (typical leakage resistance $R = 1 \times 10^6 \text{ Ohm}$)
- Extended length: 3600 mm
- Connection: 3 mm snap / banana socket
- Colour: black
- Selling unit: 1 piece

APPLICATIONS

For assembly, testing and repair of electronic assemblies at the ESD workstation.

STANDARDS AND COMPLIANCE

Suitable for grounding to IEC 61340-5-1, tested to BGI 818:2001.