

ESD earthing plug with 3x 4 mm banana socket, yellow - Safeguard WL42571

Item no. WL42571

Manufacturer Safeguard

Safeguard ESD earthing plug for EU sockets with three 4 mm banana plug sockets. A 1 M Ω safety resistor links banana plug earth leads to the protective earth in a personnel-safe way.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Yellow
Depth	60
Height	50
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.08 kg
Width	65



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Safeguard ESD earthing plug is plugged into an EU socket without a cable and provides three 4 mm banana plug sockets for earth leads. Dissipation is personnel-safe through a 1 M Ω safety resistor.

BENEFITS

- three 4 mm banana plug sockets for earth leads
- 1 M Ω safety resistor per connection
- compact housing, without cable for EU socket

TECHNICAL DATA

- Connections: 3 x 4 mm banana plug socket
- Safety resistor: 1 M Ω per connection
- Dimensions: 65 x 60 x 50 mm
- Weight: 80 g
- Mains connection: EU socket, without cable
- Colour: yellow

APPLICATION

For grounding banana plug earth leads in EPA areas of electronics manufacturing.

STANDARDS

Suitable for building ESD protected areas to IEC 61340-5-1.