

ESD earthing cable 2x 10 mm snap, 0.6 m, black - Safeguard WL42093

Item no. WL42093**Manufacturer Safeguard**

ESD earthing lead connecting ESD bench and floor matting to a common ground point. Both ends fitted with a 10 mm snap and an integrated 1 MOhm safety resistor for defined personnel and equipment protection.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Black
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This ESD earthing lead connects ESD bench and floor matting to a common ground point, providing a controlled charge path at the workstation. The 0.6 m length suits ground points located nearby.

BENEFITS

- Defined charge dissipation from ESD matting to the ground point
- Integrated 1 MOhm safety resistor protects personnel against discharge currents
- 10 mm snap connectors on both ends for fast installation

TECHNICAL DATA

- Connection: 2x 10 mm snap
- Cable length: 0.6 m
- Typical resistance: 1 MOhm safety resistor
- Colour: Black
- Sales unit: 1 piece

APPLICATIONS

For earthing ESD table mats and floor coverings in EPA zones in electronics manufacturing, repair and assembly.

STANDARDS AND COMPLIANCE

Supports an EPA built to IEC 61340-5-1.