

ESD earthing cable 2x 10 mm female snap, 4.5 m, black

Item no. WL42096

Manufacturer Safeguard

ESD earthing lead with female 10 mm snaps on both ends, connecting ESD bench and floor matting to the ground point. Integrated 1 MOhm safety resistor for defined personnel and equipment protection.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Colour	Black
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This ESD earthing lead connects ESD bench and floor matting to a common ground point, providing a controlled charge path at the workstation. The 4.5 m length bridges larger distances to the ground point.

BENEFITS

- Defined charge dissipation from ESD matting to the ground point
- Integrated 1 MOhm safety resistor protects personnel against discharge currents
- Female 10 mm snaps on both ends for common matting studs

TECHNICAL DATA

- Connection: 2x 10 mm female snap
- Cable length: 4.5 m
- Typical resistance: 1 MOhm safety resistor
- Colour: Black
- Sales unit: 1 piece

APPLICATIONS

For earthing ESD table mats and floor coverings in EPA zones in electronics manufacturing, repair and assembly.

STANDARDS AND COMPLIANCE

Supports an EPA built to IEC 61340-5-1.