

ESD earthing cable 10 mm snap/ring terminal, 3 m, black

Item no. WL42101**Manufacturer Safeguard**

ESD earthing lead with a 10 mm snap at one end and a ring terminal at the other, connecting ESD bench and floor matting to a bolted ground point. Integrated 1 MOhm safety resistor.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Colour	Black
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

This ESD earthing lead connects ESD bench and floor matting to the ground point, providing a controlled charge path at the workstation. The 10 mm snap engages the matting stud while the ring terminal bolts to an earthed screw point.

BENEFITS

- Defined charge dissipation from ESD matting to the ground point
- Integrated 1 MOhm safety resistor protects personnel against discharge currents
- Snap and ring terminal combination for bolted connection

TECHNICAL DATA

- Connection: 10 mm snap / ring terminal
- Cable length: 3 m
- Typical resistance: 1 MOhm safety resistor
- Colour: Black
- Sales unit: 1 piece

APPLICATIONS

For earthing ESD table mats and floor coverings at bolted ground points in EPA zones.

STANDARDS AND COMPLIANCE

Supports an EPA built to IEC 61340-5-1.