

## ESD earthing cable 2x 10 mm female snap, 0.15 m, black

Item no. WL24939

Manufacturer Safeguard

Short ESD earthing lead with female 10 mm snaps on both ends, connecting ESD bench and floor matting to the ground point. Integrated 1 MOhm safety resistor for defined personnel and equipment protection.

### TECHNICAL DATA

|                   |                         |
|-------------------|-------------------------|
| Ausführungsklasse | <b>ESD (antistatic)</b> |
| Certification     | <b>IEC 61340-5-1</b>    |
| Colour            | <b>Black</b>            |
| Sales unit        | <b>1 Stück</b>          |
| Weight            | <b>0.1 kg</b>           |



### STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

### DESCRIPTION

This ESD earthing lead connects ESD bench and floor matting to a common ground point, providing a controlled charge path at the workstation. The short 0.15 m length suits ground points located directly nearby.

### BENEFITS

- Defined charge dissipation from ESD matting to the ground point
- Integrated 1 MOhm safety resistor protects personnel against discharge currents
- Female 10 mm snaps on both ends, includes 2x 10 mm snap fasteners

### TECHNICAL DATA

- Connection: 2x 10 mm female snap
- Cable length: 0.15 m
- Typical resistance: 1 MOhm safety resistor
- Colour: Black
- Sales unit: 1 piece

## **APPLICATIONS**

For earthing ESD table mats and floor coverings in EPA zones in electronics manufacturing, repair and assembly.

## **STANDARDS AND COMPLIANCE**

Supports an EPA built to IEC 61340-5-1.