

Shielding bag METAL-IN, 203x406 mm, 76nm

Item no. WL24066

Manufacturer Safeguard

ESD-Abschirmbeutel METAL-IN, 203 x 406 mm, 76µm

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.0099 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

DESCRIPTION

SafeGuard's shielding ESD bag is manufactured with an outer layer of conductive polyester and an inner layer of conductive polyethylene. In addition, the material thickness is 76µm. On the ESD bag the ESD and Recycle symbol, as well as type and LOT no. are printed.

- with ESD and recycle symbol, type and LOT no.
- outside: polyester conductive
- inside: polyethylene dissipative
- Metallization: aluminium-vaporized, shielding < 15 nJ
- weldable
- film thickness: 76µm +/- 10 %

PRODUCT DETAILS

item number	WL24066
manufacturer	SAFEGUARD

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

manufacturer item number	20-873-0541
model	SafeGuard ESD
width	203 mm
height	406 mm
order unit	100 piece
colour	transparent
zip	no
film thickness	76µm +/- 10 %
property packaging	shielding