

Fully automatic ionising bar 650QAC, 24 V DC, 400 mm range, 240 mm - A1-ESD EP0402018

Item no. EP0402018

Manufacturer A1-ESD

The fully automatic 650QAC ionising bar neutralises static charges at distances up to 400 mm and can run entirely without compressed air. Recessed, user-replaceable emitters and LED alarm for cleaning and faults.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Certification **IEC 61340-5-1**Sales unit **1 Stück**Weight **0.1 kg**

STANDARDS & COMPLIANCE

IEC 61340-5-1

DESCRIPTION

The 650QAC ionising bar neutralises static charges fully automatically. A high-voltage waveform generates positive and negative ions at every emitter pin, dissipating charges reliably at distances up to 400 mm. The bar also operates without compressed air.

BENEFITS

- Fully automatic discharge in a compact body
- Range up to 400 mm, operation possible without compressed air
- Recessed emitter tips, user-replaceable
- Control via the on-device buttons or the BarMaster
- LED indicator for cleaning and fault alarm

TECHNICAL DATA

- Range: up to 400 mm
- Connection: 24 V DC, max. 500 mA
- Compressed air connection: 6 mm, max. 2 bar (optional)

STANDARDS AND COMPLIANCE

- Suitable for EPA areas to IEC 61340-5-1