

Short-range ionising bar A924IPS, 24 V DC, IP66 - A1- ESD EP0402035

Item no. EP0402035

Manufacturer A1-ESD

Compact A924IPS ionising bar with integrated power supply for short-range applications. Neutralises static charges at distances up to 200 mm, adjustable via BarMaster or SmartControl. IP66 rated.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

IEC 61340-5-1

DESCRIPTION

The A924IPS ionising bar removes static charges right where they build up in the process. Its compact body with an integrated power supply suits short-range applications where installation space is limited.

BENEFITS

- Compact design with integrated power supply, no separate high-voltage wiring needed
- Neutralises static charges at distances up to 200 mm
- Output voltage, frequency and balance adjustable via BarMaster or SmartControl
- LED status indicator with cleaning and fault signalling

TECHNICAL DATA

- Range: up to 200 mm
- Electrical connection: 4-pin M8, 24 V DC
- Compressed air connection: 6 mm, max. 2 bar
- Protection rating: IP66
- Housing: FR-ABS, titanium emitters

STANDARDS AND COMPLIANCE

- CE marking and UL certification
- Suitable for EPA areas to IEC 61340-5-1