

ESD Barcode Scanner MS852+HD 1D/2D, Corded - A1-ESD EP0201105

Item no. EP0201105**Manufacturer A1-ESD**

Corded ESD barcode scanner MS852+HD for reading all common 1D and 2D barcodes in ESD protected areas and cleanrooms. Megapixel sensor, IP42, USB connection with a 2 m cable reach.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.31 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340: 105 IEC 61340-5-1

DESCRIPTION

The ESD barcode scanner MS852+HD reliably reads 1D and 2D barcodes in the EPA and cleanroom without building up electrostatic charge. The corded megapixel sensor delivers reliable results even on damaged codes.

BENEFITS

- Suitable for use in ESD protected areas and cleanrooms
- Reads 1D and 2D barcodes, including on mobile screens
- Reads damaged or poorly printed barcodes
- Supports OCR, QR, Dot and Digimarc codes

TECHNICAL DATA

- Resistance per IEC 61340: 10^5 to 10^9 ohm
- Dimensions (L x W x H): 88 x 72 x 178 mm
- Weight: 213 g
- Interface: USB
- Protection class: IP42

- Drop protection: 2.10 m
- Cable reach: 2 m
- Service life: up to 10,000,000 triggers
- Signalling: 90 dBi beeper and LED indicator

SCOPE OF DELIVERY

- ESD scanner
- USB interface cable
- 5-year warranty

STANDARDS

Resistance per IEC 61340-5-1, suitable for ESD protected areas (EPA).