

ESD Barcode Scanner MS852 DPM 1D/2D, Corded - A1-ESD EP0201108

Item no. EP0201108 **Manufacturer** A1-ESD**Manufacturer no.** EP0201108

Corded ESD barcode scanner MS852 DPM for reading all common 1D and 2D barcodes plus special Direct Part Marks (DPM) in ESD protected areas and cleanrooms. Megapixel sensor, IP42, USB.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Execution	ESD (antistatic)
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.36 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340: 105 IEC 61340-5-1

DESCRIPTION

The ESD barcode scanner MS852 DPM reliably reads 1D and 2D barcodes plus Direct Part Marks (DPM) in the EPA and cleanroom without building up electrostatic charge. The corded megapixel sensor also reads damaged or poorly printed codes.

Benefits

- Suitable for use in ESD protected areas and cleanrooms
- Reads 1D and 2D barcodes, including on mobile screens
- Reads special symbologies such as Direct Part Marks (DPM)
- Reads damaged or poorly printed barcodes

Technical data

- Resistance per IEC 61340: 10^5 to 10^9 ohm
- Dimensions (L x W x H): 88 x 72 x 178 mm

- Weight: 165 g without cable
- Interface: USB
- Protection class: IP42
- Drop protection: 2.10 m
- Cable reach: 2.00 m
- Service life: up to 10,000,000 triggers

Scope of delivery

- ESD scanner
- USB interface cable
- 1-year warranty

Standards

Resistance per IEC 61340-5-1, suitable for ESD protected areas (EPA).