

## ESD coiled cord PRO 2 MΩ, black, 3.6 m, 7/10 mm snap

Item no. WL42089

Manufacturer Safeguard

ESD coiled cord from the PRO line for grounding wrist straps inside the EPA. Black version with a 2 MΩ safety resistor, 7/10 mm snap fastener and 3.6 m working length.

### TECHNICAL DATA

|                   |                         |
|-------------------|-------------------------|
| Ausführungsklasse | <b>ESD (antistatic)</b> |
| Certification     | <b>IEC 61340-5-1</b>    |
| Colour            | <b>Black</b>            |
| Sales unit        | <b>1 Stück</b>          |
| Weight            | <b>0.1 kg</b>           |



### STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

### DESCRIPTION

This Safeguard ESD coiled cord PRO connects a wrist strap to the EPA grounding point and dissipates personnel-bound electrostatic charges in a controlled way. The integrated 2 MΩ safety resistor limits the leakage current and protects the wearer.

### BENEFITS

- Reliable personnel grounding with a defined 2 MΩ resistance
- Stretchable coiled form for full freedom of movement
- Extended reach with 3.6 m working length

### TECHNICAL DATA

- Electrical resistance: 2 MΩ
- Length: 3600 mm (3.6 m)
- Connection: 7 / 10 mm snap fastener
- Colour: black
- Tested to BGI 818:2001
- Selling unit: 1 piece

## **APPLICATION**

For grounding ESD wrist straps at workstations in electronics manufacturing, assembly and repair.

## **STANDARDS AND COMPLIANCE**

Suitable for use in EPA areas to IEC 61340-5-1.