

ESD coil cord 2 MOhm, 1.8 m, 10/10 mm snap, black

Item no. WL42081

Manufacturer Safeguard

Highly elastic ESD coil cord for personnel grounding inside the EPA. Connects a wrist strap to the ground point via two 10 mm snaps, 1.8 m length, integrated 2 MOhm resistor.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Colour	Black
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Safeguard ESD PRO coil cord links an ESD wrist strap to the grounding point of the workstation and drains personal charges in a controlled way. The integrated resistor limits the discharge current and protects sensitive components against electrostatic discharge.

BENEFITS

- Reliable personnel grounding in the ESD protected area (EPA)
- Highly elastic coil for freedom of movement without a trip hazard
- 10 mm snaps on both ends for common wrist straps and grounding boxes

TECHNICAL DATA

- Model: Safeguard ESD PRO
- Discharge resistance: 2 MOhm
- Length: 1.8 m (stretched)
- Connection: 10 mm snap / 10 mm snap
- Colour: black
- Tested to BGI 818:2001

APPLICATION

For grounding operators at ESD workstations in electronics manufacturing, repair and assembly.

STANDARDS AND COMPLIANCE

Supports the ESD control programme to IEC 61340-5-1. Tested to BGI 818:2001.