

SG-SF-ROSA-ABL-0,09-250X400. ESD tubular film pink permanently conductive, roll, 250 mx400 mm, thickness 0.09 mm

Item no. WL24865

Manufacturer Safeguard

ESD-Schlauchfolie rosa permanent ableitend, Rolle, 250 mx400 mm, Stärke 0,09 mm

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Rose
Weight	0.0099 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

DESCRIPTION

SafeGuard's pink ESD films are ideal for the professional packaging of products within an ESD protection zone and serve primarily as dust protection. The ESD foil is printed with the ESD and recycle symbol, the lot number and the SafeGuard logo.

- Polyethylene pink with ESD and recycle symbol, LOT-No.
- amine-free, weldable, permanently conductive

PRODUCT DETAILS

item number	WL24865
manufacturer	SAFEGUARD
model	SafeGuard ESD
length	250000 mm
width	400 mm
order unit	roll

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

content unit	250 m
material	polyethylene
zip	no
property packaging	permanent dissipative
film thickness	0,09 mm
colour manufacturer	pink