

SG-LPT-ROSA-ABL-55-150X600. ESD bubble wrap, pink conductive, width 600 mm, 150 m roll

Item no. WL24846

Manufacturer Safeguard

ESD-Luftpolsterfolie rosa ableitend, Breite 600 mm, 150 m Rolle

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Certification **IEC 61340**

Colour **Rose**

Weight **0.0099 kg**



STANDARDS & COMPLIANCE

ESD safe DIN EN 610340-5-1 DIN EN 61340

DESCRIPTION

DESCRIPTION

The conductive ESD bubble wrap from SafeGuard is 2-ply and can be welded together. The knob diameter is 10 mm and of course meets the requirements of DIN EN 610340-5-1.

- Surface resistance: $R_{pp} < 1 \times 10^{10} \Omega$
- Properties: Conductive LDPE
- stud diameter: 10mm
- 2-ply
- weldable, recyclable, amine-free
- complies with DIN EN 61340 and ROHS directive

PRODUCT DETAILS

item number	WL24846
manufacturer	SAFEGUARD
model	SafeGuard ESD

length	150000 mm
width	600 mm
order unit	roll
content unit	150 m
property packaging	dissipative
film thickness	55µm +/- 10 %