

Screwdriver SoftFinish ESD Slotted 3.0 x 100 mm - Wiha 27150

Item no. WH-27150

Manufacturer Wiha

EAN 4010995271503

ESD-safe slotted screwdriver with SoftFinish handle, dissipative to IEC 61340-5-1, for all work on components susceptible to electrostatic discharge. Blade thickness 0.5 mm, slot width 3 mm, overall length 204 mm, handle diameter 23 mm. Chrome-vanadium-molybdenum steel blade, matt chrome-plated.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Country of Manufacture **Germany**HS-Code **82054000**Weight **0.032 kg**

STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

Working on electronic assemblies with slotted screws calls for a tool that fits precisely and poses no risk of electrostatic damage. This SoftFinish ESD screwdriver meets both requirements: a precision 3 mm slotted blade and certified ESD protection to IEC 61340-5-1.

BENEFITS

- ESD protection to IEC 61340-5-1, surface resistance 10^6 to 10^9 ohm
- 3 mm slot, 0.5 mm blade thickness, 100 mm visible blade length for good access
- Thoughtful handle size concept: slim 23 mm handle for small screws and fast tightening
- Hard and soft zones on the SoftFinish handle support a powerful and reliable grip
- Chrome-vanadium-molybdenum steel blade, matt chrome-plated for long service life

TECHNICAL DATA

- Slotted: 3 mm
- Blade thickness: 0.5 mm
- Round blade diameter: 3 mm
- Handle diameter: 23 mm
- Overall length: 204 mm

- Visible blade length: 100 mm
- Material: chrome-vanadium-molybdenum steel, matt chrome-plated

APPLICATIONS

Ideal for electronics manufacturing, device maintenance and laboratory work where slotted screws on ESD-sensitive components need to be loosened or tightened. Made in Germany (DEU). HS code 82054000. Standard IEC 61340-5-1.