

Screwdriver SoftFinish® Slotted Round Blade 4.5 x 125 mm for Low-Lying Screws - Wiha 00697

Item no.	WH-00697	Manufacturer	Wiha
Manufacturer no.	00697	EAN	4010995006976

The Wiha 302 SoftFinish slotted screwdriver with a 4.5 mm round blade and 125 mm length covers the common 4.5 mm screw size in mechanical and electrical engineering applications, with a 30 mm handle for adequate torque. Total length 236 mm, complementary DIN size.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
Execution	TEC
HS-Code	82054000
Weight	0.059 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The 4.5 mm slotted profile is a frequently specified size in mechanical engineering and electrical installations. The Wiha 302 SoftFinish 4.5 mm x 125 mm targets this size specifically for recessed positions: the round blade enters the slot cleanly, the 30 mm handle applies the required torque, and 125 mm of blade length gives the reach for enclosed assemblies.

Benefits

- 4.5 mm round blade precisely matched to the common screw size in mechanical and electrical engineering
- 0.8 mm cutting edge thickness for a stable, non-slip seat in the slot

- 125 mm blade length reaches recessed screw heads in housings and mounting frames
- SoftFinish® two-component handle with 30 mm diameter for ergonomic turning even under load
- Complementary size to DIN dimensions

Technical data

- Slot width: 4.5 mm
- Cutting edge thickness: 0.8 mm
- Round blade diameter: 4.5 mm
- Handle diameter: 30 mm
- Visible blade length: 125 mm
- Overall length: 236 mm

Applications

For low-lying 4.5 mm slotted screws in mechanical engineering, electrical installations, and general trade. Designed for dry environments. Complementary size to DIN dimensions.

Manufactured in Germany. HS code 82054000.