

# Screwdriver SoftFinish ESD Slotted 4.0 x 100 mm - Wiha 27151

<b>Item no.</b>	<b>WH-27151</b>	<b>Manufacturer</b>	<b>Wiha</b>
<b>Manufacturer no.</b>	<b>27151</b>	<b>EAN</b>	<b>4010995271510</b>

ESD-safe slotted screwdriver with SoftFinish handle, dissipative to IEC 61340-5-1, for work on components susceptible to electrostatic discharge. Blade thickness 0.8 mm, slot width 4 mm, overall length 211 mm, handle diameter 30 mm. Chrome-vanadium-molybdenum steel blade, matt chrome-plated.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>Germany</b>
ESD equipment	<b>ESD Schraubendreher</b>
Execution	<b>ESD (antistatic)</b>
HS-Code	<b>82054000</b>
Weight	<b>0.056 kg</b>



## STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

## DESCRIPTION

For 4 mm slotted screws on ESD-sensitive components, this SoftFinish screwdriver provides the right combination of precision fit and antistatic protection. The dissipative tool safely channels electrostatic energy away, preventing damage to sensitive parts.

## Benefits

- ESD protection to IEC 61340-5-1, surface resistance  $10^6$  to  $10^9$  ohm
- 4 mm slot, 0.8 mm blade thickness, 100 mm visible blade length
- Medium 30 mm handle diameter for higher torques when driving larger screws
- Hard and soft zones on the SoftFinish handle for optimal grip during fast turning

- Chrome-vanadium-molybdenum steel blade, matt chrome-plated for long service life

## Technical data

- Slotted: 4 mm
- Blade thickness: 0.8 mm
- Round blade diameter: 4 mm
- Handle diameter: 30 mm
- Overall length: 211 mm
- Visible blade length: 100 mm
- Material: chrome-vanadium-molybdenum steel, matt chrome-plated

## Applications

Electronics manufacturing, device maintenance and laboratory work involving medium slotted screws on ESD-sensitive assemblies. Made in Germany (DEU). HS code 82054000. Standard IEC 61340-5-1.