

Interchangeable Electric Blade Hex 3.0 mm for TorqueVario-S T Electric 136 mm, VDE - Wiha 38918

Item no. WH-38918

Manufacturer Wiha

EAN 4010995389185

The Wiha interchangeable electric blade 38918 with 3.0 mm internal hex is exclusively compatible with the Wiha TorqueVario-S T electric torque screwdriver and enables controlled tightening and loosening of screws up to 5.5 Nm. The directly moulded insulation is individually tested to IEC 60900 for safe operation up to 1,000 V AC.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	82079030
Weight	0.034 kg



STANDARDS & COMPLIANCE

IEC 60900

DESCRIPTION

This VDE-certified interchangeable electric blade in chrome-vanadium-molybdenum steel (through-hardened, blued) with directly moulded protective insulation is purpose-built for the Wiha TorqueVario-S T electric T-handle torque screwdriver. The combination of blade and T-handle delivers accurate torque on internal hex fasteners at live assemblies.

BENEFITS

- Directly moulded protective insulation: continuous insulation coverage over the blade
- Individually tested to IEC 60900: every blade verified, safe on live parts up to 1,000 V AC
- Chrome-vanadium-molybdenum steel: high strength and durability
- Torque range up to 5.5 Nm: controlled assembly of sensitive components
- slimTechnology: slim blade profile for confined installation spaces

TECHNICAL DATA

- Internal hexagon: 3.0 mm
- Torque value max.: 5.5 Nm
- Overall length: 136 mm
- Visible blade length: 35 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

- Dimensions: 136 x 20 x 20 mm
- Material: chrome-vanadium-molybdenum steel, through-hardened
- VDE certified: Yes
- Standard: IEC 60900
- Country of origin: Germany

APPLICATIONS

Industrial assembly and maintenance on live assemblies where a specified torque must be maintained. For use exclusively with the Wiha TorqueVario-S T electric torque screwdriver.

Manufactured to IEC 60900 (Germany, HS 82079030).