

## Interchangeable Electric Blade TORX T40, 136 mm, max. 20 Nm - Wiha 38936

Item no. WH-38936

Manufacturer Wiha

EAN 4010995389369

Insulated interchangeable TORX T40 blade for the Wiha TorqueVario-S T electric torque screwdriver with T-handle. The chrome-vanadium-molybdenum steel blade is through-hardened with a moulded protective insulation rated for live parts up to 1,000 V AC. Suitable for industrial assembly tasks at defined torques up to 20 Nm.

### TECHNICAL DATA

|                        |           |
|------------------------|-----------|
| Ausführungsklasse      | TEC       |
| Certification          | IEC 60900 |
| Country of Manufacture | Germany   |
| HS-Code                | 82079030  |
| Weight                 | 0.04 kg   |



## STANDARDS & COMPLIANCE

IEC 60900

## DESCRIPTION

This TORX T40 interchangeable blade pairs with the Wiha TorqueVario-S T electric for controlled fastening and loosening of large TORX fasteners at torques up to 20 Nm. The moulded protective insulation is individually tested to IEC 60900 and ensures safe work on live parts up to 1,000 V AC.

## BENEFITS

- Protective insulation moulded directly onto the blade - safe operation up to 1,000 V AC
- Chrome-vanadium-molybdenum steel blade, through-hardened and burnished
- VDE-certified, individual piece testing to IEC 60900
- TORX T40 for large fasteners, torque-controlled fastening up to 20 Nm
- Visible blade length 35 mm, overall length 136 mm

## TECHNICAL DATA

- TORX: T40
- Torque value max.: 20 Nm
- Overall length: 136 mm
- Visible blade length: 35 mm
- Product dimensions: 136 x 20 x 20 mm (L x W x D)

**esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

- Tool for electrics: Yes
- VDE certified: Yes

## **APPLICATIONS**

Compatible exclusively with the Wiha torque screwdriver with T-handle TorqueVario-S T electric. Designed for industrial assembly work with large TORX T40 fasteners requiring precise torque compliance up to 20 Nm. Made in Germany. Standard: IEC 60900.