

Screwdriver SoftFinish® ESD Slotted 5.5 x 125 mm antistatic - Wiha 08182

Item no. WH-08182

Manufacturer Wiha

EAN 4010995081829

The Wiha SoftFinish® ESD Slotted screwdriver 5.5 x 125 mm protects electrostatically sensitive components by safely dissipating static charges to IEC 61340-5-1. The large-diameter handle (30 mm) allows greater torque for driving larger slotted screws.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
ESD equipment	ESD Schraubendreher
HS-Code	82054000
Weight	0.072 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

Uncontrolled electrostatic discharges can cause severe damage to sensitive components. The Wiha SoftFinish® ESD Slotted screwdriver 5.5 x 125 mm maintains a surface resistance of 10^6 to 10^9 ohm at all times, meeting IEC 61340-5-1 requirements. The large-volume SoftFinish® handle enables higher torque application - important for larger slotted fasteners in enclosures and terminal strips.

BENEFITS

- ESD-certified to IEC 61340-5-1 - safe use on sensitive assemblies
- Dissipative discharge path 10^6 - 10^9 ohm - no abrupt discharges
- Large-volume SoftFinish® handle (dia. 30 mm) - higher torque for larger screws
- Hard and soft zones on handle - optimal force transfer for fast turning
- Chrome-vanadium-molybdenum steel, matt chrome-plated - lasting blade quality

TECHNICAL DATA

- Slot width: 5.5 mm
- Cutting strength: 1 mm
- Round blade diameter: 5.5 mm
- Visible blade length: 125 mm

- Handle diameter: 30 mm
- Overall length: 236 mm
- Surface resistance: 10^6 - 10^9 ohm

APPLICATIONS

For assembly and service work on PCBs, control cabinets, and other ESD-sensitive assemblies requiring larger slotted screws.

Made in Germany. HS code 82054000. Standard: IEC 61340-5-1.