

Screwdriver SoftFinish electric Hex Nut Driver 9.0 x 125 mm, insulated 1,000 V - Wiha 00860

Item no. WH-00860


Manufacturer Wiha

EAN 4010995008604

VDE-certified hex nut driver for external hexagon screws and hex nuts, 9.0 mm across flats with a 125 mm blade. The SoftFinish handle (Ø 36 mm) transmits hand force precisely and reduces fatigue during prolonged use. Individually piece-tested to IEC 60900 for safe work on live parts up to 1,000 V AC.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
HS-Code	82041100
Weight	0.118 kg



STANDARDS & COMPLIANCE

IEC 60900

DESCRIPTION

The 322 SoftFinish electric hex nut driver is designed for external hexagon screws and nuts of 9.0 mm across flats. The fully insulated chrome-vanadium-molybdenum blade (outside Ø 16 mm) passes individual piece testing per IEC 60900 and is approved for use on live conductors up to 1,000 V AC.

BENEFITS

- VDE and GS certified to IEC 60900 - individually tested for safe work up to 1,000 V AC
- SoftFinish handle Ø 36 mm - endorsed by the German AGR for ergonomic, fatigue-reducing work
- Wiha handle size concept - grip sized for efficient torque transfer at the 9.0 mm fastening
- Hard and soft zones on handle - support a secure grip during fast or forceful turning
- Chrome-vanadium-molybdenum steel, insulated - long-lasting strength and corrosion resistance

TECHNICAL DATA

- Hexagon size: 9.0 mm
- Outside diameter blade: 16.0 mm
- Handle diameter: 36 mm
- Visible blade length: 125 mm
- Overall length: 243 mm

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

- Material: chrome-vanadium-molybdenum steel, insulated
- Weight: 118 g

APPLICATIONS

Driving and removing 9.0 mm external hexagon screws and nuts in electrical installations, control cabinets, and industrial equipment where work is carried out on or near live parts up to 1,000 V AC.

Made in Germany. HS code: 82041100. Standard: IEC 60900.