

Screwdriver handle SoftFinish®-telescopic ESD SYSTEM 4, 4.0 mm - Wiha 31498

Item no. WH-31498

Manufacturer Wiha

EAN 4010995314989

The Wiha SoftFinish®-telescopic ESD handle accepts all SYSTEM 4 interchangeable blades (series 269) via its 4.0 mm hex socket and allows stepless blade length adjustment from 18 to 90 mm. The ClickStop ball clamp locks the blade securely and enables fast changes. Compliant with IEC 61340-5-1, surface resistance 10^6 to 10^9 ohms.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Country of Manufacture	Poland
HS-Code	84661038
Weight	0.037 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Wiha SoftFinish®-telescopic ESD handle solves the problem of reaching deep-seated screws in electronics: the telescopic socket adjusts blade length steplessly from 18 to 90 mm without needing a different tool. The ergonomic multi-component handle with anti-roll protection provides a secure, fatigue-reducing grip.

BENEFITS

- Stepless blade length 18 to 90 mm - reaches deep-seated screws without tool change
- ClickStop ball clamp - secure blade hold and fast blade swaps
- Ergonomic multi-component handle, 23 mm diameter - reduces operator fatigue
- Surface resistance 10^6 to 10^9 ohms - ESD-safe per IEC 61340-5-1
- Compatible with all SYSTEM 4 interchangeable blades (series 269)

TECHNICAL DATA

- Hexagon head: 4.0 mm
- Handle diameter: 23 mm
- Handle length: 105 mm
- Blade length adjustable: 18 to 90 mm

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

- Product dimensions: 105 x 104 x 23 mm

APPLICATIONS

For all precision screw work on electrostatically sensitive components in electronics manufacturing, instrument assembly, and precision engineering. Suitable for use in ESD protection zones.

Made in Poland (POL). Standard: IEC 61340-5-1. HS code: 84661038.