

Soft-faced Hammer Safety 40 mm Medium Soft/Hard with Hickory Handle - Wiha 26612

Item no. WH-26612

Manufacturer Wiha

EAN 4010995266127

The Wiha Safety soft-faced hammer 40 mm pairs two interchangeable 40 mm round cellulose acetate faces - medium-soft black and hard orange - with an ergonomic hickory handle. At 325 mm overall length it handles paving, tiling and drywall as well as assembly and dismantling tasks.

TECHNICAL DATA

Ausführungsklasse **TEC**

Country of Manufacture **Poland**

HS-Code **82052000**

Weight **0.621 kg**


DESCRIPTION

The Wiha Safety soft-faced hammer 40 mm delivers recoilless positioning blows while protecting delicate surfaces through its high-impact effect. The approx. 25 % greater hammer head mass increases impact power while reducing the effort required. The black medium-soft face (40 mm) suits paving, tiling and drywall construction; the orange hard face tackles assembly, dismantling and building-site or workshop work.

BENEFITS

- Recoilless operation protects joints and workpiece surfaces
- Approx. 25 % greater head mass delivers more impact power with less effort
- Two hardness grades: medium soft (black) and hard (orange), 40 mm diameter each
- Ergonomic hickory handle with non-slip surface, 325 mm overall length
- Hammer faces and handle available separately as spare parts

TECHNICAL DATA

- Hammer face diameter: 40 mm
- Overall length: 325 mm
- Hammer head height: 110 mm
- Product dimensions: 325 x 110 x 45 mm (L x W x D)
- Weight: 0.621 kg
- EAN: 4010995266127

APPLICATIONS

Paving and tiling trade, drywall construction, assembly and dismantling work, building trade and workshop. Suited for measured positioning blows on components held in machine vices.

GS tested. Made in Poland (HS 82052000).