

Soft-faced hammer dead-blow medium-hard hickory handle, 30 mm hammer face, 350 mm - Wiha 02093

Item no. WH-02093

Manufacturer Wiha

EAN 4010995020934

The Wiha soft-faced hammer 02093 delivers measured positioning blows without recoil, protecting sensitive surfaces through high-impact contact. The medium-hard yellow hammer face (30 mm diameter) suits mechanical engineering, vehicle repair, and sheet metal and assembly work. Overall length 350 mm.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Poland
HS-Code	82052000
Weight	0.436 kg



DESCRIPTION

The Wiha 800 soft-faced hammer with 30 mm hammer face combines dead-blow technology with a comfortable 350 mm handle length. The metal filling in the hammer head fully absorbs the recoil, protecting the user's joints, tendons, and muscles. The approximately 25% greater head mass increases impact effect while reducing physical effort.

BENEFITS

- Dead-blow action through metal filling protects joints and reduces the risk of injury
- Medium-hard yellow hammer face (30 mm) for controlled blows on sensitive workpieces
- Approx. 25% greater head mass for optimum impact with less physical effort
- Hickory handle with non-slip surface for a secure grip
- Hammer face and handle available separately as spare parts
- GS tested

TECHNICAL DATA

- Hammer face diameter: 30 mm
- Overall length: 350 mm
- Hammer head height: 115 mm
- Dimensions: 350 x 115 x 31 mm (L x W x D)
- Handle: hickory wood
- Standards: GS tested

APPLICATIONS

Suitable for measured positioning blows on work pieces in machine vices, vehicle repair, and sheet metal and assembly tasks. The 30 mm face offers a slightly larger contact area than the 25 mm version. Made in Poland, HS code 82052000.