

## BiCut Industrial High-Performance Diagonal Cutters DynamicJoint Switchable 200 mm - Wiha 38189

Item no. WH-38189

Manufacturer Wiha

EAN 4010995381899

The Wiha BiCut® Industrial diagonal cutters handle materials from soft to extremely hard - cables, nails, screws, wire rope, spring wire and chains. DynamicJoint® switches from 100% to 200% force at the press of a button: the same cutting result with half the hand force. Inductively hardened cutting edges at approximately 64 HRC and C70 tool steel ensure long service life. 200 mm.

### TECHNICAL DATA

|                        |              |
|------------------------|--------------|
| Ausführungsklasse      | TEC          |
| Country of Manufacture | Vietnam      |
| HS-Code                | 82032000     |
| Norm                   | DIN ISO 5749 |
| Weight                 | 0.363 kg     |



## STANDARDS & COMPLIANCE

DIN ISO 5749

## DESCRIPTION

The BiCut® Industrial is the high-performance diagonal cutter for demanding trade and industrial cutting tasks. The patented DynamicJoint® joint design doubles the available cutting force with a simple press of a button - reducing the required hand force by 50% and protecting muscles and tendons during extended use. The inductively hardened cutting edges at approximately 64 HRC in C70 tool steel ensure precise cuts and a long service life. Regular application of a drop of oil extends the tool's lifespan further.

## BENEFITS

- DynamicJoint®: switchable 100% / 200% force - hand force requirement reduced by 50%
- Inductively hardened cutting edges (approx. 64 HRC) and C70 tool steel for long service life
- Ergonomically shaped handle backs with hard and soft zones
- Cuts soft to extremely hard materials: cables, nails, bolts, wire rope, chains

## TECHNICAL DATA

- Overall length: 200 mm (8")
- Dimensions: 215 x 60 x 28 mm
- Cutting force: 21

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

- Hard wire: up to 3.5 mm
- Hardened spring steel: up to 3 mm
- Cutting edge hardness: approx. 64 HRC
- Weight: 0.363 kg

## **APPLICATIONS**

For trades, building services and industry for cutting cables, wires, screws, wire rope and chains. Based on DIN ISO 5749. Regular application of a drop of oil recommended. Made in Vietnam. HS 82032000.